

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 09-260979

(43)Date of publication of application : 03.10.1997

(51)Int.Cl.

H03F 3/68

H03F 3/217

H03F 3/30

(21)Application number : 08-072340

(71)Applicant : NISSIN ELECTRIC CO LTD

(22)Date of filing : 27.03.1996


(72)Inventor : MIZUKI KATSUFUSA
KAWAKATSU TAKESHI

(54) POWER AMPLIFIER

(57)Abstract:

PROBLEM TO BE SOLVED: To attain a high efficiency of the power amplifier to which a highly accurate amplification such as amplification of a transformer output received by a protection relay in a power distribution system is a requirement.

SOLUTION: Most power of an input voltage V_i of an input signal is amplified by a switching amplifier 22 and a feedback circuit 24 detects an error caused by the switching amplifier 22, a subtractor 25 subtracts the error from the input voltage V_i , and the result difference voltage V_d is given to a push-pull amplifier 23, and output voltages V_{o1} , V_{o2} of the two amplifiers 22, 23 are added and the sum is outputted. Thus, TRs 35, 36 are operated in a saturation region and the high efficiency switching amplifier 22 amplifies most power and TRs 43, 44 are operated in a non-saturation region and the push-pull amplifier 23 capable of high accuracy amplification is used to amplify the remaining power. Thus, high accuracy and high efficiency are attained.



LEGAL STATUS

[Date of request for examination]

18.12.2002

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office